



## AGRIMAX RT 600



### Description

AGRIMAX RT 600 is the ideal tire for grassland, harvesting and spreading applications. Thanks to its large contact area, AGRIMAX RT 600 ensures an excellent pressure distribution on the land reducing damage on grassland and protecting your soil. Thanks to its round shoulder technology, the reinforced bead and increased number of lugs, it guarantees great stability and traction.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Harvester

Version STANDARD

Tire Type TL

Tyre size 800/65R32

LI/SS 172;D

## Dimensions US Standard

USA Code	94076376
SW (US) (in)	30.5
OD (US) (in)	71.7
Rim Rec	DW 27 B
Rim Alt	DH 27 B; DW 25 B
ECE	E11-106R-0010409

## Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35
40	6540	7640	8750	9720	10700	11530	12920	13890
30	6860	8020	9190	10220	11230	12110	13570	14580
25	7150	8370	9590	10650	11720	12630	14150	15210
20	7520	8780	10060	11190	12300	13260	14860	15970
5 LT	8750	10240	11740	13040	14340	15450	17320	18620
5 HT	7520	8780	10060	11190	12300	13260	14860	15970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..