



AGRIMAX RT 945



Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ▪ Sprayer

Version STANDARD

Tire Type TL

Tyre size 380/90R50

LI/SS 160;A8/B

Dimensions US Standard

USA Code	94065479
SW (US) (in)	15.4
OD (US) (in)	76.9
SLR (US) (in)	36.3
RC (US) (in)	234.6
Rim Rec	W 12
Rim Alt	W 11; W 13
ECE	E11-106R-006446
TRA Code	R1W

Load Capacity (US)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	4070	5260	6350	7040	7440	8130	8830	9420	9920	---
25	4070	5260	6350	7040	7440	8130	8830	9420	9920	---
20	4350	5630	6800	7540	7970	8710	9460	10090	10610	---
5	5890	7610	9180	10180	10760	11760	12760	13620	14340	14880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..