



## AGRIMAX RT 855



### Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version	STEEL BELTED
Tire Type	TL
Tyre size	420/80R50
LI/SS	165;A8/B

## Dimensions US Standard

USA Code	94075508
SW (US) (in)	16.5
OD (US) (in)	76.8
SLR (US) (in)	36.0
RC (US) (in)	234.4
Rim Rec	W 13
Rim Alt	W 12
ECE	E11-106R-0010078
TRA Code	R1W

## Load Capacity (US)

mph / psi	15	17	20	23	29	35	41	46	52	58	64
30	4880	5460	6140	6700	7390	8740	8630	9310	9890	10450	11350
25	4880	5460	6140	6700	7390	7840	8630	9310	9890	10450	11350
20	5240	5840	6570	7180	7900	8400	9250	9980	10580	11190	12160
5 LT	6550	7310	8220	8980	9900	10500	11570	12490	13250	14010	15220
5 HT	5240	5840	6570	7180	7900	8400	9250	9980	10580	11190	12160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..