



MAGLIFT RIM GUARD



Description

MAGLIFT (RIM GUARD) is engineered and designed for heavy duty forklifts used in industrial and logistic facilities. The solid construction of MAGLIFT (RIM GUARD) features a high load capacity and an outstanding comfort, while its designed rim guard ensures protection against wheel damage. This tire shows excellent cut and chip resistance resulting in a longer tire life. MAGLIFT reinforced structure eliminates slippage risk whilst the special bead shape simplifies mounting operations on the rim.

UM

US Standard

Construction

◆ Solid

Machinery

Industrial & Construction ■ Forklift

Version

STANDARD

Tyre size

6.50-10

LI/SS

Dimensions US Standard

USA Code	94066308
SW (US) (in)	6.1
OD (US) (in)	22.6
Rim Rec	5.50 F - 10

Load Capacity (US)

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..