



RIDEMAX FL 699



Description

RIDEMAX FL 699 is the perfect BKT tire for road applications with trailers and tank trucks. This All Steel tire stands out for its high mileage and durability. The reinforced bead ensures better stability even at high speeds. The new RIDEMAX FL 699 also provides excellent performance in the fields. The tire has been designed with a particular focus on load capacity to decrease the number of transport cycles.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Tanker

| | |
|-----------|-------------|
| Version | STANDARD |
| Tire Type | TL |
| Tyre size | 525/65R20.5 |
| LI/SS | 173;F |

Dimensions IS Standard

| | |
|---------------|-----------------|
| OD (IS) (mm) | 1200 |
| SLR (IS) (mm) | 544 |
| RC (IS) (mm) | 3678 |
| Rim Rec | 16.00 |
| ECE | E11-54R-0018927 |

Load Capacity (IS)

| | |
|------------|------|
| km/h / bar | 8.00 |
| 80 | 6500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..