



AGRIMAX RT 765



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Sprayer

Version	SPECIAL
Tire Type	TL
Tyre size	280/70R20
LI/SS	116;A8/B

Dimensions IS Standard

SW (IS) (mm)	275
OD (IS) (mm)	900
SLR (IS) (mm)	408
RC (IS) (mm)	2705
Rim Rec	W 9
Rim Alt	W 8; W 10
ECE	E4-106R-00641
TRA Code	R1W

Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	590	675	775	875	975	1075	1165	1250
40	590	675	775	875	975	1075	1165	1250
30	630	725	835	940	1050	1155	1250	1340
10 LT	790	905	1040	1175	1310	1445	1560	1675
10 HT	630	725	835	940	1050	1155	1250	1340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..