



AGRIMAXFACTOR

Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors perfect for haulage and soil tillage operations. The improved tread design with increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance. AGRIMAXFACTOR's overall advantages are great handling in combination with driving comfort and excellent durability. The exclusive sidewall shows the "E-READY" logo that highlights BKT's commitment to electric mobility.



UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version STANDARD

Tire Type TL

Tyre size 620/70R42

LI/SS 173;D

Dimensions US Standard

USA Code	94073634
SW (US) (in)	24.6
OD (US) (in)	76.2
SLR (US) (in)	34.5
RC (US) (in)	228.5
Rim Rec	DW 20 B
Rim Alt	DW18L; W18L
ECE	E11-106R-007766
TRA Code	R1W

Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35	41	47
40	5590	6590	7590	8450	9460	10320	11320	12180	13330	14330
30	5870	6920	7980	8880	9930	10840	11890	12800	14000	15050
25	6130	7230	8320	9270	10360	11310	12400	13350	14600	15700
20	6440	7580	8740	9730	10880	11870	13030	14010	15330	16480
5 LT	7500	8840	10180	11330	12680	13830	15180	16320	17870	19200
5 HT	6440	7580	8740	9730	10880	11870	13030	14010	15330	16480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..