



WASTEMAX

Description

WASTEMAX is a solid tire developed by BKT for wheel loaders operating at scrap yards, waste handling facilities, and demolition sites. The tire's solid construction significantly reduces the risk of tyre failure from cuts, punctures, and chunks caused by sharp debris, making WASTEMAX a highly cost-effective solution. Moreover, the particularly cut-and-chip-resistant compound offers exceptional protection against abrasive materials, while the deep tread design maximizes tyre life and reduces machine downtime. WASTEMAX features a reinforced bead structure that prevents rim slippage in challenging waste-handling operations. In addition, sidewall apertures provide an excellent cushioning effect, ensuring a smoother ride and improved operator comfort during long service hours.



UM

US Standard

Construction

◆ Solid

Machinery

OTR ■ Loader

Version

STANDARD

Tyre size

23.5-25

LI/SS

Dimensions US Standard

USA Code	94518265
OD (in)	64.2
Rim Rec	19.50/2.5

Load Capacity (US)

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..