



IS standard



GROWING TOGETHER

# AW 726



PRODUCT DATA SHEET



Bias



### Technologies



Block Pattern

### Performance



Durability



Self-Cleaning



# AW 726

AW 726 has been specially designed for trailers in transport operations. It is best suited for both on-and-off-the-road usage. AW 726 shows excellent road performance and self-cleaning features. The block pattern design provides an extended tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 15.3"	11.5/80 - 15.3	9.00	-	300	855	363	2531	AB	14	TL	126 A8	139 A8
	11.5/80 - 15.3	9.00	-	300	855	363	2531	STD	14	TL	126 A8	139 A8
	11.5/80 - 15.3	9.00	-	300	855	373	2540	SB	14	TL	126 A8	139 A8
Ø 15.5"	400/60 - 15.5	AG 13.00	-	400	875	-	-	STD	18	TL	137 A8	149 A8
Ø 17"	420/55 - 17	13.00	-	415	890	392	2584	STD	-	TL	121 A8	133 A8

AB: Aramid Belted - STD: Standard - SB: Steel Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling