



IS standard



GROWING TOGETHER

CRANE SPECIAL



PRODUCT DATA SHEET



Bias



CRANE SPECIAL



CRANE SPECIAL is suitable for pick & carry cranes on rough terrains. The tire is made of a special compound which provides high stability and durability.

Technologies



High Speed



Special Compound

Performance



Stability

	Tire size	Type	STAR RATING	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 24"	14.00 - 24	TL	24	-	STD	375	1368	628	4050	10.00 W	-
	14.00 - 24	TT	24	-	STD	375	1368	628	4050	10.00 W	-
Ø 25"	16.00 - 25	TL	28	-	STD	463	1485	682	4395	11.25/2.0	-
	16.00 - 25	TT	28	-	STD	463	1485	682	4395	11.25/2.0	-
	18.00 - 25	TL	32	-	STD	510	1615	739	4780	13.00/2.5	15.00/2.5

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference