



IS standard



GROWING TOGETHER

# AGRIMAX ELOS



PRODUCT DATA SHEET



Radial

R-2

B

178

Technologies



Extra Deep Tread

Performance



For muddy ground



Traction



Self-Cleaning



# AGRIMAX ELOS

🇬🇧 AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 28"	420/85 R 28 (16.9 R 28)	139 A8/B	W 15 L	W 13 ; W 14 L	438	1467	665	4349	675	STD
Ø 34"	480/70 R 34	155 A8/155 B	W 15 L	W 16 L ; W 14 L	500	1605	733	4868	750	STD
Ø 38"	340/85 R 38 (13.6 R 38)	133 A8/B	W 12	W 11	353	1602	735	4774	750	STD
	380/85 R 38 (14.9 R 38)	139 A8/B	W 12	W 11 ; W 13	380	1662	772	4994	775	STD
	420/85 R 38 (16.9 R 38)	144 A8/B	W 15 L	W 13 ; W 14 L	438	1735	785	5135	800	STD
	480/80 R 38 (18.4 R 38)	149 A8/B	W 16 L	W 15 L ; DW 16 L	489	1803	821	5356	825	STD
Ø 42"	710/70 R 38	178 A8/B	DW 23 B	DW 25 B	716	2019	915	6103	925	STD
	480/80 R 42 (18.4 R 42)	151 A8/B	DW 16 L	DD 16 L ; W 16 L	489	1890	857	5629	875	STD
	520/85 R 42 (20.8 R 42)	157 A8/B	DW 16 L	DD 18 L ; DW 18 L	516	1988	904	5865	925	STD
Ø 46"	520/85 R 42 (20.8 R 42)	167 A8/B	DW 16 L	DD 18 L ; DW 18 L	516	1988	920	6095	925	STD
	520/85 R 46	169 A8/169 B	DW 16 L	DW15L;DW18L; W15L;W16L; W18L;DD16L; DD18L	530	2075	957	6293	975	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index