



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 23



PRODUCT DATA SHEET



Radial

G-2/L-2

A8

186

Technologies



All Steel

Performance



Traction



Self-Cleaning



Durability



EARTHMAX SR 23

RADIAL OTR TIRES

EARTHMAX SR 23 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders. It features superior forward and lateral traction as well as exceptional self-cleaning properties. The durable casing and the particularly cut-resistant tread provide a long service life.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
													Rec.	Alt.
Ø 25"	15.5 R 25	TL	G-2/L-2	*	146 A8/ 169 A2	CRC	-	383	1264	559	3756	27	12.00/1.3	-
	17.5 R 25	TL	G-2/L-2	*	153 A8/ 176 A2	CRC	-	448	1345	612	4108	27	14.00/1.5	-
	20.5 R 25	TL	G-2/L-2	*	161 A8/ 186 A2	CRC	-	535	1490	668	4489	31	17.00/2.0	-

CRC: Cut Resistance Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference