



## BK-LOADER 53

### Description

BK-LOADER 53 is an aramid-belted tire designed for loaders in industrial applications. The unique tread design provides best lateral stability in addition to extended tread wear and extraordinary resistance against cuts and punctures thanks to the extra deep tread. BK-LOADER 53 features outstanding self-cleaning properties as well as excellent grip and traction on both wet and dry surfaces. This tire is particularly suitable for recycling operations.



### UM

IS Standard

### Construction

 Radial

### Machinery

Industrial & Construction ■ Loader

Version ARAMID BELTED

Tire Type TL

Tyre size 365/365R18

LI/SS 146A2/142A4;

## Dimensions IS Standard

SW (IS) (mm)	360
OD (IS) (mm)	990
SLR (IS) (mm)	458
RC (IS) (mm)	3017
Rim Rec	11

## Load Capacity (IS)

km/h / bar	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5
<b>20 TRANSPORT</b>	930	1195	1405	1620	1855	2045	2255	2440	2650
<b>10 LOADING</b>	1050	1350	1590	1830	2100	2310	2550	2760	3000
<b>STATIC</b>	1670	2150	2530	2910	3340	3675	4055	4390	4770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..