



IS standard



GROWING TOGETHER

RIB 713



PRODUCT DATA SHEET



Radial



Technologies



High Speed



IF Technology



Steel Belted

Performance



Durability



Fuel Economy



High Load Capacity



Stubble Resistance



RIB 713

RIB 713 is a steel-belted tire for agricultural implements. As a response to the increasing awareness of low soil compaction in modern farming, RIB 713 has been designed with IF technology. This enables the tire to carry heavier loads at lower inflation pressures and provides a larger footprint with uniform weight distribution. The steel-belted structure provides excellent puncture resistance and hence increased protection against stub penetration and relative damage, even if running into strong stubble. In addition, "D" speed rating (65 km/h - 40 mph) allows for fast road transfers. RIB 713 is BKT's contribution to maximize both the productivity and efficiency of your farming business.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 15"	IF 240/80 R 15	129 D	W 8	-	240	765	354	2324	360	SR
	IF 265/85 R 15 (10.5 L R 15)	121 D	W 8	-	260	831	368	2502	390	SR
	IF 280/70 R 15	128 D	W 8	-	279	779	347	2356	360	SR
	IF 280/70 R 15	134 D	W 8	-	279	779	347	2356	360	SR
	IF 320/70 R 15	146 D	W 10	-	320	823	367	2590	390	SR

SR: Stubble Resistant



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index