



CRANE SPECIAL



Description

CRANE SPECIAL is suitable for pick & carry cranes on rough terrains. The tire is made of a special compound which provides high stability and durability.

UM

IS Standard

Construction

 Bias

Machinery

Industrial & Construction ■ Mobile Crane

Version STANDARD

Tire Type TT

Tyre size 16.00-25

LI/SS

Dimensions IS Standard

OD (IS) (mm)	1485
SLR (IS) (mm)	682
RC (IS) (mm)	4395
Rim Rec	11.25/2.0
TRA Code	E3

Load Capacity (IS)

km/h / bar	5.75
50	6700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..