



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 35



PRODUCT DATA SHEET



Radial

E-3/L-3

B

214

Technologies



All Steel



Block Pattern

Performance



Traction



High Load Capacity



Comfort



Durability



Stability



Cut Resistance



# EARTHMAX SR 35

RADIAL OTR TIRES

EARTHMAX SR 35 is a low-profile All Steel radial tire specially designed for articulated dump trucks and wheel loaders. It is ideal for operations requiring exceptional traction and flotation. EARTHMAX SR 35 provides both excellent traction and stability. Thanks to its strong steel-belted casing, it ensures extraordinary durability and resistance to snags and punctures. The tire is available as cut-resistant compound for a maximum service life even under severe conditions.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	650/65 R 25 (25/65 R 25)	TL	E-3/L-3	**/*	180 B/ 193 A2	CRC	202	635	1498	669	4493	39	19.50/2.5	-
	650/65 R 25 (25/65 R 25)	TL	E-3	**	180 B	CRC	202	635	1498	669	4493	39	19.50/2.5	-
	650/65 R 25 (25/65 R 25)	TL	L-3	*	193 A2	CRC	-	635	1498	669	4493	39	19.50/2.5	-
	750/65 R 25 (30/65 R 25)	TL	E-3/L-3	**/*	190 B/ 202 A2	CRC	223	740	1601	715	4802	42	24.00/3.0	22.00/3.0 ; 25.00/3.0
	750/65 R 25 (30/65 R 25)	TL	E-3	**	190 B	CRC	223	740	1601	715	4802	42	24.00/3.0	22.00/3.0 ; 25.00/3.0
	750/65 R 25 (30/65 R 25)	TL	L-3	**	209 A2	CRC	-	740	1601	715	4802	42	24.00/3.0	22.00/3.0 ; 25.00/3.0
Ø 29"	775/65 R 29	TL	E-3/L-3	**/*	195 B/ 206 A2	CRC	220	775	1752	787	5311	45	24.00/3.5	24.00/3.0 ; 25.00/3.5
	775/65 R 29	TL	E-3	**	195 B	CRC	220	775	1752	787	5311	45	24.00/3.5	24.00/3.0 ; 25.00/3.5
	775/65 R 29	TL	L-3	*	206 A2	CRC	-	775	1752	787	5311	45	24.00/3.5	24.00/3.0 ; 25.00/3.5
	775/65 R 29	TL	L-3	**	213 A2	CRC	-	775	1752	787	5311	45	24.00/3.5	24.00/3.0 ; 25.00/3.5
	875/65 R 29 (35/65 R 29)	TL	E-3/L-3	**/*	203 B/ 214 A2	CRC	279	890	1860	816	5559	48	27.00/3.50	27.00/3.0 ; 28.00/3.5
	875/65 R 29 (35/65 R 29)	TL	E-3	**	203 B	CRC	279	890	1860	816	5559	48	27.00/3.50	27.00/3.0 ; 28.00/3.5
	875/65 R 29 (35/65 R 29)	TL	L-3	*	214 A2	CRC	-	890	1860	816	5559	48	27.00/3.50	27.00/3.0 ; 28.00/3.5

CRC: Cut Resistance Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference