

# Technische gegevens A2 DUO

	Categorie I2E+		Categorie I3+	
	Methaan 20/25 mbar		Butaan 29 mbar	Propan 37 mbar
Gasaansluiting	3/8"		3/8"	3/8"
Dubbelwandige rookafvoer in mm	Ø100 / Ø150		Ø100 / Ø150	Ø100 / Ø150
Afremring in mm	/		/	/
Nominaal vermogen in kW	6,5		6	5,85
Capaciteit in m <sup>3</sup>	59 - 105		54 - 97	53 - 95
Belasting in kW O.W.	7,6		7	6,75
Gasconsumptie in m <sup>3</sup> /h (15°C - 1013 mbar)	0,805		0,217	0,277
Voordruk en mbar	20	25	29	20
Branderdruk vollast in mbar	13,7	17	21,4	13,7
Branderdruk kleinstand in mbar	6	7	7,5	6
Primaire lucht in mm	2 x (2 x Ø9)	2 x (2 x Ø4)	2 x (2 x Ø13)	2 x (2 x Ø9)
Insp. in 100e x lengte	170 x 22 / 185 x 22		100 x 22 / 120 x 22	100 x 22 / 120 x 22
Insp. waakvlam n°	45		33	33
Rendementsklasse	1		1	1
Elektrische spanning	6VDC			
Afmetingen (H×L×D) in mm	739 × 668 × 338			
Gewicht in kg	98			

