

R O W A N

# Kelly

by Sarah Hatton



## YARN

Rowan Kid Classic

12 x 50gm

(photographed in Smoke 831)

## NEEDLES

1 pair 4mm (no 8) (US 6) needles

1 pair 4½mm (no 7) (US 7) needles

## BUTTONS

8 x 00410

## TENSION

22 sts and 28 rows to 10cm over st st on 4½mm (US 7) needles.

## BACK

Using 4mm (US 6) needles cast on 108 sts. Knit 8 rows.

Change to 4½mm (US 7) needles.

**Next row:** Knit 23, m1, K3, m1, knit to last 26 sts, m1, K3, m1, knit to end. 112 sts.

**Row 1 (WS):** P17, K3, P10, K3, purl to last 33 sts, K3, P10, K3, purl to end.

**Row 2:** Inc in 1st st, K19, C4B, K2, C4F, knit to last 30 sts, C4B, K2, C4F, knit to last 2 sts, inc in next st, K1. 114 sts.

**Row 3:** P18, K3, P10, K3, purl to last 34 sts, K3, P10, K3, purl to end.

Row 4: Inc in 1 st st, knit to last 2 sts, inc in next st, K1. 116 sts.

These 4 rows set side seam shaping and cable panels.

Work 57 rows as set, inc 1 st at each end of every foll alt row as set and ending with a WS row. 172 sts.

**Next row:** Inc in 1st st, patt until half of first cable panel has been worked, turn and leave rem sts on a holder. 56 sts.

**Next row:** K1, patt to end.

This row sets g st on cable panel.

Working on these sts only, work 13 rows in patt as set, inc 1 st at side edge as before and ending with a RS row. 63 sts.

Break off yarn and leave these sts on a holder.

With RS facing, rejoin yarn to sts previously left on holder and work in patt until half of second cable panel has been worked, turn and leave rem sts on a holder. 62 sts.

**Next row:** K1, patt to last st, K1.

This row sets g st on cable panel.

Work 13 rows in patt as set, ending with a RS row.

Break off yarn and leave these sts on a holder.

With RS facing, rejoin yarn to rem sts and patt to last 2 sts, inc in next st, K1. 56 sts.

**Next row:** Patt to last st, K1.

This row sets g st on cable panel.

Working on these sts only, work 13 rows in patt as set, inc 1 st at side edge on next and every foll alt row, ending with a RS row. 63 sts.

**Next row (WS):** Patt 63 sts, patt across centre 62 sts on holder, then patt across 63 sts on second holder. 188 sts.

Cont in patt as before across all sts, inc 1 st at each end of next and every foll alt row until there are 250 sts.

Work 15 rows without shaping, ending with a WS row.

## Shape shoulders

Cast off 4 sts at beg of next 2 rows. 242 sts.

Cast off 5 sts at beg of next 2 rows. 232 sts.

Cast off 6 sts at beg of next 6 rows. 196 sts.

Cast off 7 sts at beg of next 4 rows. 168 sts.

Cast off 8 sts at beg of next 4 rows. 136 sts.

Cast off 9 sts at beg of next 4 rows. 100 sts.

Cast off 10 sts at beg of next 2 rows. 80 sts.

## Shape back neck

Next row: Cast off 10 sts, patt until there are 14 sts on needle, turn and leave rem sts on a holder.

**Next row (WS):** Cast off 4 sts, patt to end.

Cast off rem 10 sts.

With RS facing, rejoin yarn to rem sts, cast off 32 sts, patt to end.  
Complete to match first side of neck, reversing all shapings.

#### LEFT FRONT

Using 4mm (US 6) needles cast on 59 sts.

Work 8 rows in g st.

Change to 4½mm (US 7) needles.

Next row: Knit 23, m1, K3, m1, knit to last 10 sts and leave these 10 sts on a holder. 51 sts.

**Row 1 (WS):** P18, K3, P10, K3, purl to end.

**Row 2:** Inc in 1st st, K19, C4B, K2, C4F, knit to end. 52 sts.

**Row 3:** P18, K3, P10, K3, purl to end.

**Row 4:** Inc in 1st st, knit to end. 53 sts.

These 4 rows set side seam shaping and cable panel.

Work 57 rows as set, inc 1 st at beg of every foll alt row as set and ending with a **WS** row. 81 sts.

**Next row:** Inc in 1st st, patt until half of cable panel has been worked, turn and leave rem sts on a holder. 56 sts.

Next row: K1, patt to end.

This row sets g st on cable panel.

Working on these sts only, work 13 rows in patt as set, inc 1 st at side edge as before and ending with a RS row. 63 sts.

Break off yarn and leave these sts on a holder.

With RS facing, rejoin yarn to sts previously left on holder and work in patt to end. 26 sts.

**Next row:** Patt to last st, K1.

This row sets g st on cable panel.

Work 13 rows in patt as set, ending with a RS row.

Next row (WS): Patt 26 sts, then patt across 63 sts on holder. 89 sts.

Cont in patt as before across all sts, inc 1 st at beg of next and every foll alt row until there are 120 sts.

Work 15 rows without shaping, ending with a WS row.

Shape shoulder

**Next row:** Cast off 4 sts, patt to end. 116 sts.

Work 1 row.

**Next row:** Cast off 5 sts, patt to end. 111 sts.

Work 1 row.

Cast off 6 sts at beg of next and foll alt row. 99 sts.

Shape neck

**Next row (WS):** Cast off 6 sts, patt to end. 93 sts.

**Next row:** Cast off 6 sts, patt to last 2 sts, K2tog. 86 sts.

**Next row:** P2tog, patt to end. 85 sts.

Cast off 7 sts at beg of next and foll alt row AT SAME TIME dec 1 st at neck edge in next 4 rows. 67 sts.

Cast off 8 sts at beg of next and foll alt row AT SAME TIME dec 1 st at neck edge in next and foll alt row. 49 sts.

Work 1 row.

**Next row:** Cast off 9 sts, patt to last 2 sts, K2tog. 39 sts.

Work 1 row.

**Next row:** Cast off 9 sts, patt to end. 30 sts.

Work 1 row.

Cast off 10 sts at beg of next and foll alt row.

Work 1 row.

Cast off rem 10 sts.

#### RIGHT FRONT

Using 4mm (US 6) needles cast on 59 sts.

Work 8 rows in g st.

Change to 4½mm (US 7) needles.

**Next row:** Knit 10, leave these 10 sts on a holder, K23, m1, K3, m1, knit

to end. 51 sts.

**Row 1 (WS):** P17, K3, P10, K3, purl to end.

**Row 2:** K21, C4B, K2, C4F, knit to last 2 sts, inc in next st, K1. 52 sts.

**Row 3:** P18, K3, P10, K3, purl to end.

**Row 4:** Knit to last 2 sts, inc in next st, K1. 53 sts.

These 4 rows set side seam shaping and cable panel.

Work 57 rows as set, inc 1 st at end of every foll alt row as set and ending with a RS row. 81 sts.

Next row: Patt until half of cable panel has been worked, turn and leave rem sts on a holder. 26 sts.

Next row: K1, patt to end.

This row sets g st on cable panel.

Working on these sts only, work 13 rows in patt as set, ending with a RS row.

Break off yarn and leave these sts on a holder.

With RS facing, rejoin yarn to sts previously left on holder and work in patt to last 2 sts, inc in next st, K1. 56 sts.

Next row: Patt to last st, K1.

This row sets g st on cable panel.

Work 13 rows in patt as set AT SAME TIME inc 1 st at end of next and every foll alt row as before. 63 sts.

Next row (WS): Patt 63 sts, then patt across 26 sts on holder. 89 sts.

Cont in patt as before across all sts, inc 1 st at end of next and every foll alt row until there are 120 sts.

Work 16 rows without shaping, ending with a RS row.

Shape shoulder

**Next row:** Cast off 4 sts, patt to end. 116 sts.

Work 1 row.

**Next row:** Cast off 5 sts, patt to end. 111 sts.

Work 1 row.

Cast off 6 sts at beg of next and foll alt row. 99 sts.

Shape neck

**Next row (RS):** Cast off 6 sts, patt to end. 93 sts.

**Next row:** Cast off 6 sts, patt to last 2 sts, P2tog. 86 sts.

**Next row:** K2tog, patt to end. 85 sts.

Cast off 7 sts at beg of next and foll alt row AT SAME TIME dec 1 st at neck edge in next 4 rows. 67 sts.

Cast off 8 sts at beg of next and foll alt row AT SAME TIME dec 1 st at neck edge in next and foll alt row. 49 sts.

Work 1 row.

**Next row:** Cast off 9 sts, patt to last 2 sts, P2tog. 39 sts.

Work 1 row.

**Next row:** Cast off 9 sts, patt to end. 30 sts.

Work 1 row.

Cast off 10 sts at beg of next and foll alt row. 10 sts.

Work 1 row.

Cast off rem 10 sts.

#### Buttonband

Using 4mm (US 6) needles work in g st across 10 sts left on holder for left front AT SAME TIME inc 1 st at side nearest left front piece. 11 sts.

Work in g st until band fits up front edge to start of neck shaping sewing in position at same time, ending with a WS row.

Break yarn and leave these sts on a holder.

Mark positions for 7 buttons on this band – first to come 2cm up from cast on edge and last to come just below neck shaping.

#### Buttonhole band

Using 4mm (US 6) needles work in g st across 10 sts left on holder for right front AT SAME TIME inc 1 st at side nearest right front piece. 11 sts.

Work to match buttonband with the addition of 7 buttonholes worked to correspond with positions marked for buttons as follows:-

**Buttonhole row (RS):** K4, cast off 2 sts (to make buttonhole – cast on 2 sts over these cast off sts on next row), knit to end.

When band is complete do not break off yarn.

### Collar

With RS facing and 4mm (US 6) needles work across 11 sts of buttonhole band, pick up and knit 20 sts up front neck, 39 sts from back neck, 20 sts down front neck and knit 11 sts from button band. 101 sts.

Work in g st until collar meas 6cm, ending with a WS row.

Next row: K4, cast off 2 sts (to make buttonhole – cast on 2 sts over these cast off sts on next row), knit to end.

Cont until collar meas 8 cm, ending with a RS row.

Cast off knitways on **WS**.

### Belt

Using 4mm (US 6) needles cast on 18 sts.

**Row 1:** Knit.

**Row 2:** K4, P10, K4.

**Row 3:** K4, C4B, K2, C4F, K4.

**Row 4:** As row 2.

These 4 rows set patt.

Cont in patt until belt meas 147cm, ending with 4th row of patt.

Cast off.

### Armhole borders

Join sides of garment to top of garter stitch.

Join shoulder seam.

With RS facing, using 4mm (US 6) needles or circular needle if required, pick up and knit 273 sts around armhole edge.

Knit 2 rows.

Cast off knitways on **WS**.

