

ConCar

Hochleistungs - Schmalkeilriemen DIN 7753/ ISO 4184 - ummantelt

High Capacity Narrow V- Belts DIN 7753/ ISO 4184 - wrapped

| Profil/ Section SPB | | | Profil/ Section SPB | |
|--|--|--|--|--|
| LW/LD= Richtlänge pitch length mm | | | LW/LD= Richtlänge pitch length mm | |
| 1250 | | | 5300 | |
| 1320 | | | 5600 | |
| 1350 | | | 6000 | |
| 1400 | | | 6300 | |
| 1450 | | | 6700 | |
| 1500 | | | 7100 | |
| 1550 | | | 7500 | |
| 1600 | | | 8000 | |
| 1650 | | | Gewicht/ weight = 0,194 kg/m | |
| 1700 | | | | |
| 1750 | | | | |
| 1800 | | | | |
| 1850 | | | | |
| 1900 | | | | |
| 1950 | | | | |
| 2000 | | | Profil/ Section SPC | |
| 2020 | | | LW/LD= Richtlänge pitch length mm | |
| 2060 | | | | |
| 2120 | | | 2000 | |
| 2150 | | | 2120 | |
| 2180 | | | 2240 | |
| 2240 | | | 2360 | |
| 2285 | | | 2500 | |
| 2300 | | | 2650 | |
| 2360 | | | 2800 | |
| 2391 | | | 3000 | |
| 2410 | | | 3150 | |
| 2430 | | | 3250 | |
| 2500 | | | 3350 | |
| 2530 | | | 3550 | |
| 2550 | | | 3620 | |
| 2580 | | | 3750 | |
| 2600 | | | 4000 | |
| 2650 | | | 4100 | |
| 2680 | | | 4250 | |
| 2730 | | | 4400 | |
| 2750 | | | 4500 | |
| 2800 | | | 4750 | |
| 2850 | | | 5000 | |
| 2900 | | | 5300 | |
| 2950 | | | 5600 | |
| 3000 | | | 6000 | |
| 3070 | | | 6300 | |
| 3150 | | | 6700 | |
| 3170 | | | 7100 | |
| 3200 | | | 7300 | |
| 3250 | | | 7500 | |
| 3350 | | | 8000 | |
| 3450 | | | 8500 | |
| 3485 | | | 9000 | |
| 3550 | | | 9500 | |
| 3650 | | | 10000 | |
| 3750 | | | 10600 | |
| 3870 | | | 11200 | |
| 4000 | | | 11800 | |
| 4060 | | | 12500 | |
| 4250 | | | | |
| 4310 | | | | |
| 4370 | | | | |
| 4500 | | | | |
| 4750 | | | | |
| 4870 | | | | |
| 5000 | | | | |
| Gewicht/ weight = 0,194 kg/m | | | Gewicht/ weight = 0,360 kg/m | |