Sicad S.p.A.
Via Caduti della Liberazione, 57
21040 Uboldo (VA) – Italia
Tel: +39 02 964121 Fax: +39 02 96412294
Web: www.eurocel.it

PRODUCT INFORMATION
EUROCEL FG 10

DESCRIPTION

Medium tensile mono-directional fiber glass reinforced single sided tape.

PRODUCT DATA

Backing	Glass fiber reinforced + BOPP film
Adhesive	Synthetic rubber and resins

	Unit	Value	Method
Total thickness	mm	0.110	PSTC 133
Adhesion to steel	N/25mm	21	PSTC 101
Tensile strength MD	N/25mm	700	PSTC 131
Elongation at break	%	6	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

Medium tensile mono-directional reinforced tape suitable for bundling and carton reinforcement, even used to bundle metal plates or bars.

Features	Benefits	
Synthetic rubber and resins adhesive	✓ High adhesion in most situations	✓ Excellent application results on different surfaces
Mono-directional glass fiber reinforced backing	✓ Good resistance to break ✓ Easy handling	✓ High security in application

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

Società Italiana Cellophane Adesivo
P.I. e C.F. IT 00220060123
Iscrizione R.E.A. Varese n. 129175
Reg. Imprese Varese n. 00220060123
Capitale Sociale € 15.000.000 i.v.