

**Brand New Replacement Product,for pos printer use ,with 3 pin din connector, works as genuine parts, 100% OEM Compatible!!**

**Full 12 months warranty**

Model Number	24V Switching Power Supply
Input Voltage Range	100-240 VAC 50/60 Hz
Peak Output Power	24W
Load Regulation	±3% over rated current: 1—6 Amps
Output Voltage Nominal	24V DC
Current	1A 2A 2.5A 3.5A 4A 5A 6A etc
Input Connector	IEC320 C6 3 pin input connector , allows cords for any country to be used
Output plug	5.5 x 2.1 mm barrel connector
Output Polarity	Center Positive
Dimensions	50mm x 32 mm x 90mm (2 inch x 1.25 inch x 3.5 inch)
OEM	Available
	Double Insulated
DC tips can be chosen	5.5 mm OD x 2.5 mm ID type 2, 5.5 mm OD x 2.5 mm ID Barrel round 3 pin din connector
Other features	Short circuit, over voltage and over current protection
Ripple noise	500Mv max
Temperature	0° to 40° C Operating
<b>MeanTime Between Failures</b>	100,000 hours at 25°C full load
<b>Testing</b>	<ul style="list-style-type: none"> <li>• 100% HI-POT tested</li> <li>• 100% cyclic Burn-In</li> </ul>
<b>Use for</b>	Pos printer,LCD TV,CCTV,LED,audio, GPS, and CB equipment.
<b>Advantages:</b>	<b>Inexpensive switchmode AC switching power supply AC/ DC converter.</b>
	<b>Efficiency &gt;85%, depending on input voltage, and output power.</b>
	<b>Inexpensive fully regulated power supply with 3 prong input</b>

