

BUY ON
www.cablematic.com

			P/NO.:	BNC-BNC				
1	CONNECTOR	BNC MALE/75ohm GOLD	CUSTOMER:					
2	CABLE	RG6/5CFB-75ohm	CUST. P/N.:	BNC-BNC				
L	25CM &50CM &1M &2M &3M &5M &10M &15M &20M &30M		APP.	Eric	UNITS	m/m		
1.0	NEW DRAWING		2008/12/24	CHK.	Carmen	DATE	2008/12/24	DES.: BNC(M)/(M) RG6/5CFB-75ohm
VER.NO.	DESCRIPTION		DATE	DRAW.	Christina	SHEET	1/1	DRAW NO.: BNC-BNC VER 1.0

TECHNICAL SPECIFICATION


CABLE TYPE

STRUCTURE

Conductor	Composition(No./mm)	1/1.02mm	
	Material	Copper Covered Steel Wire	
	Outside Diameter (mm)	1.02±0.03mm	
Insulation	Material	Gas Injected Foamed Polyethylene	
	Thickness (mm)	1.78mm	
	Nom. Diameter(mm)	4.57± 0.15mm	
Shield	Material	(1) Bonded Aluminum Foil	(2) Aluminum Wire
	Construction	0.025mm	16*7/0.12mm
	Coverage	76%	
	Diameter(mm)	5.05±0.05mm	
Jacket	Material	RoHS PVC	
	Diameter(mm)	6.9±0.15mm	
	Color	Black	

ELECTRICAL CHARACTERISTIC

Impedance	Ω	75 ±3						
Insulation Resistance	MΩ / km	1000 ↑						
Capacitance	pF/M	53 ±3						
Attenuation	Frequency(MHz)	300	400	600	865	1000	1450	2050
	dB/100M	11.64	12.63	16.73	18.54	21.49	26.5	33.10



DRWN.	JOYCE HSU	DRWN. No.:
CHKD.	C.H.LIU	
APPD.	VINCENT SHEN	Date: MAR.24, 2014