



NO. 序号	P/NAME 品名	DESCRIPTION 品名规格	QTY 数量
1	线材	UL2919 28AWG*3COAX+28AWG*9C+AL+1+B OD: 8.5±0.15 贝吉色羊雾 (K306) L: 1900mm	1
2	线材	UL2464 28AWG*4C+1+AL OD:3.0±0.10 双倍长L:700MM	1
3	插头	HD15P 公头 PC99蓝色胶芯	2
4	插头	USB "A" TYPE 白胶芯 焊接式	1
5	插头	MD6P 公头 PC99 绿色胶芯	1
6	螺丝	10. 7*16*28mm	11g
7	CORE	PE袋:0. 6*7"*10"	44g
			6g
			27g
			44g
			4
			1

TOL	< 30	: ±0.1	UNIT : mm	FINISHING	PART NO.	Ver.	A0			
	30 < 120	: ±0.15								
	120 < 315	: ±0.2	3RD ANGLE'S	MATERIAL	MOLD NO.	KVM-17C-08-AST	Qty	1		
	315 <	: ±0.3								
	ANGLE TOL	: ±0.5°	APPROVED		TITLE	KVM-17C-08-AST 1 to 2 Cable				
			CHECKED		DRAWING NO.	1 to 2 -Cable.				
			DESIGNED		SIZE	A3	SCALE		SHEET:	OF
			DRAWN	Chenhaijing	07-12-10					