




**Notes:**

1. Plug: JT-SZ3 10A 250V~ Clear Injection, no scratch and dirt
2. Cable: H05VV-F 3G0.75mm<sup>2</sup> Jacket  $\phi 6.5 \pm 0.1$  Conductor  $42 \times 0.15$ , Core  $\phi 2.4 \pm 0.1$   
Cable Mark:  VDE  H05VV-F 3G0.75mm<sup>2</sup>
3. Test: Hi-Pot: Inner Voltage AC2500V/1S, External Voltage AC4500V/1S, current leakage 1mA, insulation resistance no less than 50M $\Omega$ , no strike out;

3	CH73	H05VV-F 3G0.75mm <sup>2</sup>	5m	Black
2	CH72	H05VV-F 3G0.75mm <sup>2</sup>	3m	Black
1	CH71	H05VV-F 3G0.75mm <sup>2</sup>	2m	Black
Item	Customer Model	Model/no	Length(m)	Color

[www.cablematic.com](http://www.cablematic.com)

P.N		Item		Drw.N	JT-YP-0101
Dre By	WANG JUNFEN			Date	2014.3.20
Check By			.x'±0.05 .xx'±0.15 .xxx'±0.25	比例	1 : 1
				投影	
					mm
					A