

2U industrial sever Rackmount Chassis



Introduction

CasePro 2U industrial server rackmount chassis KI-N2066 Cooling is essential as so many use 2U as small servers; the KI-N2066 has 4* 8cm ball bearing cooling fans that create positive air pressure within the case. There are 2x 5.25" exposed and 9 internal 3.5" hard drive bays. The compact size, and cooling make it as an excellent choice. The universal rear window could use Riser card or lowprofile card together

Features and Benefits

- Up to 2x 5.25" drivebay+9x3.5" HDD drivebay
- Innovation universal window for all kind of expansion !
- Front access USB2.0*2
- Standard I/O shield
- Standard PS-2 ATX



Specification

Dimension (W*H*D)	19"*3.5"*26"/ 482*88.9*660(mm)
Material Construction	Heavy-duty and anti-rusty SECC steel,thickness:1.0mm
M/B Size	12"*13" (EEB)
Expansion	Universal expansion for low profile add-on card and riser card together
Control & Indicator	1*Power switch +1* Reset switch 1 x LED (power) +2 x LED (HDD) 2*2.0 USB
Cooling Fans	3*8cm Fan in middle
DriveBay	3 x 5.25" + 1 x 3.5" (external) + 9 x 3.5" (internal)
Power Supply	Standard PS-2 ATX Power supply 300w~550w
Sliding rail	26" ball bearing sliding rail (option)
Color	Black / Red / Bule / Green / Silver
Operation Temperature	Up to 50C (122°F)
Operation Humidity (Non-condensing)	Up to 90%
Packing Measurement CBF / CBM	2.3/ 0.065
Packing N.W / G.W	10.5KGS /12.5.0KGS

www.casepro.cn

