



Notes;

- 1.Plug: JT003 16A 250V~ Clear injection, no scratch and dirt
- 2.Cable:H05VV-F 3X1.5mm Jacket  $\phi 8 \pm 0.2$  Conductor  $48 \times 0.2$ ,  
Core  $\phi 32 \pm 0.1$   
Cable Mark :  $\triangleleft$ VDE  $\triangleright$  H05VV-F 3X1.5mm<sup>2</sup>
- 3.Test: Hi-Pot : Inner Voltage AC2500V/1S、 External Voltage AC6000V/1S、 current leakage 1mA, insulation resistance no less than  $50M\Omega$ , no strike out

| 5    | CL14           | H05VV-F 3x1.5mm <sup>2</sup> | 10000±50mm | Black |
|------|----------------|------------------------------|------------|-------|
| 4    | CL13           | H05VV-F 3x1.5mm <sup>2</sup> | 5000±50mm  | Black |
| 3    | CL12           | H05VV-F 3x1.5mm <sup>2</sup> | 3000±30mm  | Black |
| 2    | CL11           | H05VV-F 3x1.5mm <sup>2</sup> | 1800±20mm  | Black |
| 1    | CL10           | H05VV-F 3x1.5mm <sup>2</sup> | 1000±10mm  | Black |
| Item | Customer Model | Model/No.                    | Length(mm) | Color |



|          |  |   |       |        |    |
|----------|--|---|-------|--------|----|
| P.N      |  | Item  |       | Drw. N |    |
| Dre By   |  |   |       | Date   |    |
| Check By |  | .xx±0.15 .x'±0.15<br>.xx±0.25 .xx'±0.25<br>.xxx±0.38 .xxx'±0.38 | 1 : 1 |        | mm |
|          |  |   |       |        |    |