



Notes;

- 1.Plug: JT-3 Clear injection, no scratch and dirt
- 2.Cable:SJT 3X18AWG jacket $\phi 8 \pm 0.1$ Conductor 4/7/0.15, Core $\phi 2.92 \pm 0.1$ Cable Mark :
Core $\phi 2.4 \pm 0.1$
Mark: (UL) E308842 SJT 3/C 18AWG(0.824mm²) 105℃ 300V VW-1 108540-001
(UL) E323736 SJT 3/C 18AWG(0.824mm²) 105℃ FT1 SHANGYU JINTAO
- 3.Test: Hi-Pot : Inner Voltage AC2500V/1S、 External Voltage AC6000V/1S、 current leakage 1mA, insulation resistance no less than 50M Ω , no strike out

5	CL67		1800±10mm	White
4	CL64		5000±25mm	Black
3	CL63		3000±15mm	Black
2	CL62		1800±10mm	Black
1	CL61		400±10mm	Black
Item	Customer Model	Model/No.	Length(mm)	Color
P. N		Item	Drw. N	
Dre By			Date	2015. 3. 23
Check By		.x±0.15 .x'±0.15 .xx±0.25 .xx'±0.25 .xxx±0.38 .xxx'±0.38	比例 1 : 1	mm
			投影	