



Notes;

- 1.Plug: JT-SZ3 Clear injection, no scratch and dirt
- 2.Cable:SJT 3X18AWG jacket  $\phi 8 \pm 0.1$  Conductor 47/0.15, Core  $\phi 2.92 \pm 0.1$  Cable Mark :  
Core  $\phi 2.4 \pm 0.1$   
Mark: (UL) E308842 SJT 3/C 18AWG(0.824mm<sup>2</sup>) 105<sup>o</sup>c 300V VW-1 108540-001  
(UL) E323736 SJT 3/C 18AWG(0.824mm<sup>2</sup>) 105<sup>o</sup>c FT1 SHANGYU JINTAO
- 3.Test: Hi-Pot : Inner Voltage AC2500V/1S, External Voltage AC6000V/1S, current leakage 1mA, insulation resistance no less than 50M $\Omega$ , no strike out

1	CL61		400 $\pm$ 10mm	Black
Item	Customer Model	Model/No.	Length(mm)	Color
P. N	Item		Drw. N	
Dre By			Date	2015. 3. 23
Check By	.x $\pm$ 0.15 .x' $\pm$ 0.15 .xx $\pm$ 0.25 .xx' $\pm$ 0.25 .xxx $\pm$ 0.38 .xxx' $\pm$ 0.38	比例	1 : 1	mm
		投影		