



1394 4P MALE



PIN ASSIGNMENT

1394 4M		4M
1	—	1
2	—	2
3	—	3
4	—	4
SHELL	—	SHELL

NO.	DESCRIPTION	Q'TY
1	CABLE:28AWG(30/0.08)*2C+32AWG(11/0.05)*1P DD:1.2*3.2mm JACKET COLOR:BLACK	1
2	IEEE1394 4PIN MALE SHELL PLATED:NICKEL CONTACT:G/F	1
3	IEEE1394 4PIN MALE SHELL PLATED:NICKEL CONTACT:G/F	1
4	55P PVC MOLDING BLACK IN COLOR	
5	RETRACTABLE NADE OF ABS BLACK IN COLOR(Pushbutton)	1

UNLESS OTHERWISE SPECIFIED TOLERANCE		DRAWN NAME: <b>競捷-EX43</b>
ANG.	±5°	
0.	±0.5	PRODUCT NO.
.0	±0.3	
.00	±0.2	FILE NAME:
SCALE:	NONE	
DRAWN	XIEBO	09/01/06
CHECKED	Xing Fa	09/01/06
APPROVED	/ /	
DATE	09/01/06	
SIZE	A4	REV. A

A	1394 RETRACTION	09/01/06
REV.	DESCRIPTION	DATE