



- Dimension:220*100*40.3mm
- Application: for SSI
- Watt:400W
- PFC:Active

Feathers :

- For 1U Ver2.3, output :400W(560W Max)
- AC input full range
- High efficiency
- 12V for +12V1,+12V2
- Low ripple & noise
- Output over voltage protection
- Short circuit protection on all outputs
- Internal 4CM FAN*2
- 100% burn-in under high ambient temperature(50°C)
- MTBF:100K hours at 25°C

BUY ON
www.cablematic.com

DC Connectors :




20+4P for M/B




4+4pin +12V CPU



4Pin for HDD



4Pin for FDD



SATA Connector

Input Sepsifications :

- AC INPUT:100-240V
- Frequency:47-63Hz
- Current:8A @100-240Vac 47Hz-63Hz

Output Specification :

- Maximum Power:400W
- Color: Black/Silver
- Cooling System:SPEED: 9500RMP(+/-10%)
DIMENSION:100*220*40.6mm
4CM fan*2
- Noise:22dB at 2500rpm
- P.G Signal:100-500ms
- Hold-up Time:17ms(min)
- Efficiency: 75%

Output :

Output Voltage	Min. load	Max. load	Load Reg.	Ripple & Noise
-12V	0.0A	0.5A	±10%	120mV P-P
+3.3V	0.1A	28.0A	±5%	50mV P-P
+5V	0.2A	35.0A	±5%	50mV P-P
+5Vsb	0.0A	2.5A	±5%	50mV P-P
+12V	0.1A	18.0A	±5%	120mV P-P
+12V2	0.5A	14.0A	±5%	120mV P-P

- +3.3V & +5V total output shall not exceed 120W.
- +3.3V & +5V & +12V1 total output shall not exceed 385W