



Specification :

1. Connector Type : FC Multimode
2. Connector Type : MT/RJ Multimode
3. Cable Type :
3-1 Zipcord cable, $\phi 1.8\text{mm}$, 62.5/125um Multimode
3-2 Cable Jacket : Orange color, PVC material
4. Cable Marker
5. Shrink Tube
6. Length : xM

Performance :

- a. Insertion Loss : $< 0.5 \text{ dB}$
- b. Fiber Extention : $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
- c. Ferrule End-face Radius : $10 < R < 25\mu\text{m}$
- d. Apex Offset : $< 50\mu\text{m}$
- e. Increase in insertion loss after 500 mating : 0.2 dB Max
- f. Operation Temperature : -20°C to $+70^\circ\text{C}$
- g. Storage Temperature : -40°C to $+80^\circ\text{C}$

FJ3x

GENERAL TOLERANCE OF DIMENSIONS X.XXX ± 0.005 X.XX ± 0.05 X.X ± 0.1	DRAWING	12.MAY.2008	ZCY	
	CHECK	12.MAY.2008	DAY	
	APPROVAL	12.MAY.2008	YTY	
		DATE	NAME	ITEM NO.: F0PC-FCMTRJ-MD-L
	SCALE	1/1 (A4)	UNIT	mm
				DES.: FC to MT/RJ Duplex patch cord
			DRAWING NO.	13-DMM1F26-xM(SA1)
			DRAWING CLASSIFICATION	S SHEET 1 OF 1

