

# SPECIFICATION

Customer :	Item : BF( R) 65	Date : 11-Apr-06
------------	------------------	------------------

<p><b>Mechanical Assembly</b></p> <p style="text-align: center;">D (Core diameter)</p>	<p><b>Ref. No :</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="3" style="text-align: center;">Dimension</th> </tr> <tr> <td style="width: 10%;">A</td> <td style="width: 15%;">32.50</td> <td style="width: 75%;">±1.00mm</td> </tr> <tr> <td>B</td> <td>17.50</td> <td>±1.00mm</td> </tr> <tr> <td>C</td> <td>19.50</td> <td>±1.00mm</td> </tr> <tr> <td>D</td> <td>6.50</td> <td>±0.50mm</td> </tr> <tr> <td>E</td> <td></td> <td></td> </tr> <tr> <td>F</td> <td></td> <td></td> </tr> <tr> <td>G</td> <td></td> <td></td> </tr> <tr> <td>H</td> <td></td> <td></td> </tr> </table>	Dimension			A	32.50	±1.00mm	B	17.50	±1.00mm	C	19.50	±1.00mm	D	6.50	±0.50mm	E			F			G			H		
Dimension																												
A	32.50	±1.00mm																										
B	17.50	±1.00mm																										
C	19.50	±1.00mm																										
D	6.50	±0.50mm																										
E																												
F																												
G																												
H																												

Electrical Requirement			
Impedance	MIN 130	Test Frequency	25 MHz
Impedance	MIN 275	Test Frequency	100 MHz
Impedance		Test Frequency	

**Test equipment : HP 4191A**

	<p>Wire : AWG#22x12cm</p> <p>Winding : 1 Turn</p> <p>Material : EC5B Nickel/Zinc</p>
--	--

**REMARK :**

Approved by	Checked by	Reported by	Approved by Customer