

	1	2	3	4	5	6	7	8	9	
	REV.	REMARK	DATE	SIGN.						
								RoHS		
	<p>MATERIAL RoHS COMPLIANT:</p> <p>1.CABLE: CONDUCTOR: 30 AWG SOLID SILVER PLATED COPPER. INSULATION: SKIN-FOAM-SKIN PAIR: 2 WIRES, WH AND YE PARALLEL. CORE: 8 PAIRS PAIR DRAIN WIRE: #0.2mm (32AWG) TINNED COPPER. PAIR SHIELD: ALUMINUM FOIL OVERLAPPED, ALU INSIDE. INNER SHIELD: ALUMINUM FOIL OVERLAPPED, APPLIED LONGITUDINALLY. OUTER SHIELD: 0.1mm DIA TINNED COPPER BRAID, 85% COVERAGE. DIAMETER: 6.1 ± 0.2 mm PRINT LEGEND: "LEONI High Speed Cable ParaLink®-14 1000 8pairs 30AWG (SHIELDED)(UL) E116441 CL2 75°C" DIFFERENTIAL IMPEDANCE: 100±5 OHM.</p> <p>2.CONNECTOR: P1,P2: Mini SAS HD 4x CABLE PLUG (SFF-8644) (1) P.C.B: 4 LAYERS, GOLD PLATING ON CONTACT PADS, WITHOUT CARBON (P/N: MPCB-040113LF REV.A / SPCB-040114A) (2) LATCH: STAINLESS STEEL (3) BACKSHELL: ZINC DIE CASTING HOOD/ NICKEL PLATING (4) PULL TAB: NYLON UL94V-0, COLOR: BLUE. (5) EMI GASKET. 3.FOR SAS 12.0 Gbps. 4.TWO-WIRED SERIAL MEMORY: ATMEL AT24C02B EEPROM (256 BYTES).</p>									
	DESC. Mini SAS HD 4x/Mini SAS HD 4x CABLE ASS'Y		APPROVED	CHECKED	DESIGNED	TOLERANCE	SCALE	*	UNIT mm	
	P/N UASS-RC005983 CUSTOMER P/N				Sino		DATE 01/23/13	DWG NO: DWG\RC\5983		

	1	2	3	4	5	6	7	8	9																																																																																																				
	REV.	REMARK	DATE	SIGN.																																																																																																									
	WIRING DIAGRAM																																																																																																												
	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4">HIGH SPEED SIGNAL</th> </tr> <tr> <th colspan="2">P1(Mini SAS HD 4x Plug)</th> <th colspan="2">P2(Mini SAS HD 4x Plug)</th> </tr> <tr> <th>PIN</th> <th>SIGNAL</th> <th>PAD</th> <th>SIGNAL</th> </tr> </thead> <tbody> <tr><td>A4</td><td>RX1+</td><td>C4</td><td>TX1+</td></tr> <tr><td>A5</td><td>RX1-</td><td>C5</td><td>TX1-</td></tr> <tr><td>A7</td><td>RX3+</td><td>C7</td><td>TX3+</td></tr> <tr><td>A8</td><td>RX3-</td><td>C8</td><td>TX3-</td></tr> <tr><td>B4</td><td>RX0+</td><td>D4</td><td>TX0+</td></tr> <tr><td>B5</td><td>RX0-</td><td>D5</td><td>TX0-</td></tr> <tr><td>B7</td><td>RX2+</td><td>D7</td><td>TX2+</td></tr> <tr><td>B8</td><td>RX2-</td><td>D8</td><td>TX2-</td></tr> <tr><td>C4</td><td>TX1+</td><td>A4</td><td>RX1+</td></tr> <tr><td>C5</td><td>TX1-</td><td>A5</td><td>RX1-</td></tr> <tr><td>C7</td><td>TX3+</td><td>A7</td><td>RX3+</td></tr> <tr><td>C8</td><td>TX3-</td><td>A8</td><td>RX3-</td></tr> <tr><td>D4</td><td>TX0+</td><td>B4</td><td>RX0+</td></tr> <tr><td>D5</td><td>TX0-</td><td>B5</td><td>RX0-</td></tr> <tr><td>D7</td><td>TX2+</td><td>B7</td><td>RX2+</td></tr> <tr><td>D8</td><td>TX2-</td><td>B8</td><td>RX2-</td></tr> <tr><td colspan="2">GND GROUP GND</td><td colspan="2">GND GROUP GND</td></tr> </tbody> </table>				HIGH SPEED SIGNAL				P1(Mini SAS HD 4x Plug)		P2(Mini SAS HD 4x Plug)		PIN	SIGNAL	PAD	SIGNAL	A4	RX1+	C4	TX1+	A5	RX1-	C5	TX1-	A7	RX3+	C7	TX3+	A8	RX3-	C8	TX3-	B4	RX0+	D4	TX0+	B5	RX0-	D5	TX0-	B7	RX2+	D7	TX2+	B8	RX2-	D8	TX2-	C4	TX1+	A4	RX1+	C5	TX1-	A5	RX1-	C7	TX3+	A7	RX3+	C8	TX3-	A8	RX3-	D4	TX0+	B4	RX0+	D5	TX0-	B5	RX0-	D7	TX2+	B7	RX2+	D8	TX2-	B8	RX2-	GND GROUP GND		GND GROUP GND		<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">LOW SPEED SIGNAL & POWER</th> </tr> <tr> <th>P1,P2(Mini SAS HD 4x Plug)</th> <th>SIGNAL</th> </tr> </thead> <tbody> <tr><td>A1</td><td>Reserved</td></tr> <tr><td>A2</td><td>IritL</td></tr> <tr><td>B1</td><td>Vact</td></tr> <tr><td>B2</td><td>ModPrsL</td></tr> <tr><td>C1</td><td>SCL</td></tr> <tr><td>C2</td><td>SDA</td></tr> <tr><td>D1</td><td>Vact</td></tr> <tr><td>D2</td><td>Vman</td></tr> </tbody> </table>					LOW SPEED SIGNAL & POWER		P1,P2(Mini SAS HD 4x Plug)	SIGNAL	A1	Reserved	A2	IritL	B1	Vact	B2	ModPrsL	C1	SCL	C2	SDA	D1	Vact	D2	Vman
HIGH SPEED SIGNAL																																																																																																													
P1(Mini SAS HD 4x Plug)		P2(Mini SAS HD 4x Plug)																																																																																																											
PIN	SIGNAL	PAD	SIGNAL																																																																																																										
A4	RX1+	C4	TX1+																																																																																																										
A5	RX1-	C5	TX1-																																																																																																										
A7	RX3+	C7	TX3+																																																																																																										
A8	RX3-	C8	TX3-																																																																																																										
B4	RX0+	D4	TX0+																																																																																																										
B5	RX0-	D5	TX0-																																																																																																										
B7	RX2+	D7	TX2+																																																																																																										
B8	RX2-	D8	TX2-																																																																																																										
C4	TX1+	A4	RX1+																																																																																																										
C5	TX1-	A5	RX1-																																																																																																										
C7	TX3+	A7	RX3+																																																																																																										
C8	TX3-	A8	RX3-																																																																																																										
D4	TX0+	B4	RX0+																																																																																																										
D5	TX0-	B5	RX0-																																																																																																										
D7	TX2+	B7	RX2+																																																																																																										
D8	TX2-	B8	RX2-																																																																																																										
GND GROUP GND		GND GROUP GND																																																																																																											
LOW SPEED SIGNAL & POWER																																																																																																													
P1,P2(Mini SAS HD 4x Plug)	SIGNAL																																																																																																												
A1	Reserved																																																																																																												
A2	IritL																																																																																																												
B1	Vact																																																																																																												
B2	ModPrsL																																																																																																												
C1	SCL																																																																																																												
C2	SDA																																																																																																												
D1	Vact																																																																																																												
D2	Vman																																																																																																												
	<p>GND GROUP 1: P1-A3,A6,A9,B3,B6,B9, P2-C3,C6,C9,D3,D6,D9</p> <p>GND GROUP 2: P1-C3,C6,C9,D3,D6,D9, P2-A3,A6,A9,B3,B6,B9</p>																																																																																																												
	Connector Shell		Connector Shell																																																																																																										
	DESC. Mini SAS HD 4x/Mini SAS HD 4x CABLE ASS'Y		APPROVED	CHECKED	DESIGNED	TOLERANCE	SCALE	*	UNIT mm																																																																																																				
	P/N UASS-RC005983 CUSTOMER P/N				Sino		DATE 01/23/13	DWG NO: DWG\RC\5983																																																																																																					