



HD15F-HD15F

HD15M

PIN ASSIGNMENT

HD15M	HD15F	HD15F
1	1	1
2	2	2
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
8	8	8
9	9	9
10	10	10
11	11	11
12	12	12
13	13	13
14	14	14
15	15	15

SHELL ——— SHELL ——— SHELL

ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTE:100%.
- 2.INSULATION RESISTANCE:DC 300V AT 10ms R>20MΩ
- 3.CONTACT RESISTANCE:<3Ω .

No.	DESCRIPTION	UNIT	Q'TY
6	THUMB SCREW #4-40UNC PLATED:GOLD ABS COLOR:BLACK	PCS	2
5	THUMB NUT #4-40UNC PLATED:GOLD	PCS	2
4	HIGH DENSITY D-SUB 15P MALE PLATED: GOLD	PCS	1
3	UL2919 30AWG*3C+24AWG*9C+AM+D+B DD8.5 COLOR:BLACK		
2	PVC MOLDED BLACK IN COLOR		
1	HIGH DENSITY D-SUB 15P FEMALE PLATED: GOLD	PCS	2

UNLESS OTHERWISE SPECIFIED TOLERANCE  
 ANG. ±5  
 0. ±0.5  
 .0 ±0.3  
 .00 ±0.2

SCALE: NONE UNIT: mm

DRAWN eric xu 06/06/15

CHECKED //

APPROVED //

DRAWN NAME:

SPL-15M-Fx2-1FT

PRODUCT NO.

FILE NAME:

REV.	DESCRIPTION	DATE
A		06/06/15

SIZE A4 REV. A