



DVI24+1F-HDMI 19F

ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTE:100%.
- 2.CURRENT RATING:1.5AMP.
- 3.INSULATION RESISTANCE:DC 500V AT 10ms R>50MΩ
- 4.CONTACT RESISTANCE:<1Ω .

SHELL	SHELL	SHELL
PIN24	PIN24	12
PIN23	PIN23	10
PIN22	PIN22	11
PIN21	PIN21	
PIN20	PIN20	
PIN19	PIN19	8
PIN18	PIN18	7
PIN17	PIN17	9
PIN16	PIN16	19
PIN15	PIN15	17
PIN14	PIN14	18
PIN13	PIN13	
PIN12	PIN12	
PIN11	PIN11	5
PIN10	PIN10	4
PIN9	PIN9	6
PIN7	PIN7	16
PIN6	PIN6	15
PIN5	PIN5	
PIN4	PIN4	
PIN3	PIN3	2
PIN2	PIN2	1
PIN1	PIN1	3
DVI 24+1M	DVI 24+1F	HDMI 19F

No	DESCRIPTION	UNIT	Q'TY
7	THUMB NUT #4-40UNC PLATED:GOLD	PCS	2
6	THUMB SCREW #4-40UNC PLATED:GOLD ABS COLOR:BLACK	PCS	2
5	DVI 24+1 MALE SOLDER COLOR:BLACK SHELL PLATED:GOLD	PCS	1
4	UL2919 30AWG*3C+24AWG*9C+AM+D+B ØØ8.5 COLOR:BLACK	PCS	1
3	PVC MOLDED BLACK IN COLOR		
2	DVI 24+1 FEMALE PLATED: GOLD	PCS	1
1	HDMI 19P FEMALE PLATED: GOLD	PCS	1

UNLESS OTHERWISE SPECIFIED TOLERANCE
 ANG. ±5'
 0. ±0.5
 .0 ±0.3
 .00 ±0.2

SCALE: 1:1 UNIT: mm

DRAWN ERIC XU 06/06/15

CHECKED / /

APPROVED / /

DRAWN NAME: SPL-D25M-FH19F-1FT

PRODUCT NO.

FILE NAME:

REV.	DESCRIPTION	DATE	SIZE	REV.
A		06/06/15	A4	A