



NOTE:
 1. TESTING CONDITIONS:
 A: INSULATION RESISTANCE 10M Ω
 B: VOLTAGE: DC300V
 C: CONDUCTOR RESISTANCE 3 Ω
 2. DURATION: 0.01S

JX75	9280- JX75	Cable OFC 5*RCA-M/M(10M)	10000±200
JX74	9280- JX74	Cable OFC 5*RCA-M/M(7M)	7000±150
JX73	9280- JX73	Cable OFC 5*RCA-M/M(5M)	5000±100
JX72	9280- JX72	Cable OFC 5*RCA-M/M(3M)	3000±80
JX71	9280- JX71	Cable OFC 5*RCA-M/M(1.5M)	1500±50
CUST.P/N	MF.P/N	SPEC	"L"

⑦	AR	OVER MOLDING COLOUR: PVC BLUE	
⑥	4	METAL HOOD SHELL:MATERIAL:ALUMINUM,PRINTING "DIGITAL"RED	
⑤	2	METAL HOOD SHELL:MATERIAL:ALUMINUM,PRINTING "DIGITAL"GREEN	
④	2	METAL HOOD SHELL:MATERIAL:ALUMINUM,PRINTING "DIGITAL"BLUE	
③	2	METAL HOOD SHELL:MATERIAL:ALUMINUM,PRINTING "DIGITAL"WHITE	
②	10	RCA PLUG GOLD PLATED CONTACT & SHELL,INSULATION:BROWN	
①	1	CABLE:[1/0.650FC+FPE+AL+26#(64/0.160FC)OD:6.0]*3F+[28#(10/0.120FC)+AL+28#(48/0.120FC) OD:6.0]*2F PVC JACKET COLOR:BLUE	
NO.	Q' TY	Description	Remark

THIS DRAWING IS A CONTROLLED DOCUMENT.			
DATE: 2007/06/08		PART NO. :	
UNITS: MM		TITLE : Cable OFC 5*RCA-M/M	
Samuel	Kevin	Standly	Michael
APPD BY	CHECK BY	ENG BY	DRAWN BY
DRAWING NO.:			
SCALE: NONE		SHEET: 1 OF 1	
REV: A0			