



### Features

- Short depth design of 470 mm only
- Build in keyboard ( 104 keys ) and Touch pad ,
- Integrated KVM console featuring a 17" LCD monitor in 1U high rack mountable Slideaway housing.
- DDC emulation of the LCD monitor- VGA settings of connected computer are automatically adjusted for optimal output to the LCD monitor.
- Standard rack mount kit included.
- Optional single or “ one man ” installation slides for easy , quick installation
- With Key lock
- Internal power built in.
- LCD Resolution 17" (1280 x 1024), support DDC2B

### LCD

- Display Type : 17" SXGA TFT LCD
- Resolution : 1280 x 1024
- Max.color : 16.7M
- Luminance : 300 cd/m2
- View Angle : 178°(H) , 178°(V)
- Pixel Pitch : 0.264 x 0.264 mm
- Contrast Ratio : 1000 : 1
- Response Time : 5 ms
- Power Consumption : 21.9 W
- LCD MTBF : 50,000hrs

### Specifications

Function		KVM-1701S
Computer connections	Direct	1
Connector Computer	Power	AC Inlet
	VGA	HD-15 Female (Blue)
	Mouse	MD-6 Female (Green)
	keyboard	MD-6 Female (purple)
Button / Switch	Power Switch	Rock Switch
	LCD adjustment	Button
LED Indicator	Power	1 (Green)
	Num Lock	1 (Green)
	Caps Lock	1 (Green)
	Scroll Lock	1 (Green)
Emulation	Keyboard	PS/2
	Mouse	
Resolution	17" LCD	1280x1024@75HZ;DDC2B
Power Input Rating		100-240VAC;50/60Hz;1A
Power Consumption	17" LCD	37W
Environment	Operating Temperature	0~40°C
	Store Temperature	-20-60°C
	Humidity	0-80% RH,NC
Physical Property	Frame	Heavy duty steel
	Weight	16.5KG
	Dimension(W*D*H)	465*470*42mm

## Ordering Information

KVM-1701S	1U Rackmount 17" TFT LCD w/1 port KVM switch,w/48w power supply
OMI-KIT	One man installation kit

## Dimension Diagram

