



The Das Console range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring , troubleshooting and software upgrades.
Push & pull out lcd module, make for simple and hassle free operation.
Cost efficient for space limited, Integrated 8" A-Grade LCD panels, combo DB15 , 8 or 16 port KVM switch & with an option remote IP console.

Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.




Features

- Support combo interface,VGA-USB & VGA-PS/2.
- Durable 80-key keyboard and touch pad.
- Cost efficient and Short depth design suit for mobile rack and limited space.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.
- Access Control List (ACL) security function for up to 8 independent user accounts.




Rear of KVM-0808-AST



Rear of KVM-0816-AST

Part No.		KVM-0808-AST	KVM-0816-AST
Direct no. of Computers		8	16
Maximum no. of Computers		232(Daisy Chain)	240(Daisy chain)
LCD	Size	8"	
	Backlight	LED	
	Resolution	1024*768	
	Max.color	262K	
	Luminance	250cd/m2	
	View Angel (H/V)	150 / 150	
	Contrast Ratio	700 : 1	
Port Selection		Push Button,OSD or Hotkey	
Expansion Slot		Yes, option for Remote IP Access	
KB/Mouse Emulation		USB & PS2	
Rack Depth		380mm to 650mm (rack cabinet front rails to rear rails)	
Power		100-240V AC 50/60Hz via IEC Type power cord	
Environment		Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP	
Physical Dimensions / Net Weights		448.5x43.6x381mm (WxHxD) / 6.5kg	448.5x43.6x381mm (WxHxD) / 7kg
Packing Dimensions / Gross		600x195x515mm (WxHxD) / 9.5kg	600x195x515mm (WxHxD) / 10kg
Accessory			
1.8meter IEC Type Power Cord			
Option Relate Item			
CVU-018	1.8meter 2-in-1 KVM Cable-USB&VGA	CVP-018	1.8meter 3-in-1 KVM Cable-PS/2&VGA
CVU-030	3.0meter 2-in-1 KVM Cable-USB&VGA	CVP-030	3.0meter 3-in-1 KVM Cable-PS/2&VGA
CVU-050	5.0meter 2-in-1 KVM Cable-USB&VGA	CVP-050	5.0meter 3-in-1 KVM Cable-PS/2&VGA
DIP-101	KVM over IP module for Remote Bios Level Access		

Rear of KVM-0808-AST



Rear of KVM-0816-AST

