



BUY ON
www.cablematic.com

NOTE: THE WORDS "Designed for Professionals" AND "DATA TRANSFER SWITCH" MUST BE PARALLED
All relevant materials are complied with RoHS directive .

DB9 M (I/O)	6132 SWITCH	DB9 F A&B
1	1	1
2	2	2
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
8	8	8
9	9	9
SHIELD		SHIELD

No.	DESCRIPTION	Q'TY	Supplier
7	PLASTO-VISCO-ELASTIC BODY	4	M562
6	SCREW 3*6PWB	4	M805
5	METAL CASE, THICKNESS 0.8mm	1set	M315
4	UL1007 26AWG INSULATOR, LENGTH 150mm	29	M541
	MAIN HEART 2-16-2	1	M94
	SCREW 4*12.5mm WITH PAD	1set	M94
	KNOB FOR A, B, SWITCH	1	M155
3	HEX-NUT 4.75*12.3mm, SCREW CAP 6.35*2.3	6set	M95&M193
2	DB9 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M108
1	DB9 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	2	M108

APPROVED		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm
CHECKED	HU	
DRAWING	JUDY	

DATE	24/JUN/13	ITEM NO.	6132	UNIT:mm	
------	-----------	----------	------	---------	--

CHECKED