

PCI 32bit 2 Serial 1 Parallel Card (RS232)

Features:

- Multi-function PCI Bus Specification 2.2 and Power Management 1.0 compliant
 - Two full-duplex asynchronous channels
 - IEEE1284 EPP parallel port
 - Multi-function target PCI controller facilitates using generic device drivers in combo applications
 - 128-byte deep FIFO per transmitter and receiver
-
- Supports Big Endian byte-lane conversion
 - Supports Plug and Play using optional non-volatile configuration memory (EEPROM)
 - Pass-through function supports 8/32-bit Local Bus running asynchronous to PCI clock
 - UARTs, Local Bus and Parallel port configured with IO or memory base address
 - Local Bus offers up to 4 chip selects mapped to 4-256 bytes of I/O and 4-16K of memory address space
 - 12 multi-purpose IO pins which can be configured to interrupt input pins
 - Serial ports offer Good-Data status
 - Flexible baud rate clock prescaler
 - Isochronous mode using external x1 baud rate
 - Automated in-band flow control using programmable Xon/Xoff in both directions
 - Automated out-of-band flow control using CTS#/RTS# and DSR#/DTR#
 - Readable flow control status and FIFO levels
 - Arbitrary FIFO thresholds for interrupts and automatic flow control
 - Supports 5, 6, 7, 8 and 9 bit data framing
 - 5.0V operation
 - Support 98se/ME/NT/2000/XP/linux
 - 160 TQFP package

