

## Express Card Serial ( USB Based & PCI-E Based)



### 952ECBR2

2 Port Serial(RS232)

2 Port Serial(422/485)

#### Features

- Supports the standard RS-232 Serial Interface
- Supports automatic handshake mode
- Supports Windows
- Provides Dual Buffers for upstream and down stream data transfer

- RS-232 (DB 9-pin male serial port ) interface
- Supports various serial devices like modems, PDAs, cellular phone, digital cameras, card readers, and more

### Specifications

#### Serial communication

- Interface RS-232
- Controller OXFORD OXPCIe952
- Bus PCI-Express one lane (x1) Express Card 34mm Wide
- No. of port 1 ports
- Port Type DB9 Male
- IRQ & IO Assigned by System
- FIFO 128K byte DMA FIFO
- Baud rate 96bps ~ 460Kbps
- Flow Control None, Xon/Xoff, RTS/CTS

#### Driver Support

- Microsoft Windows 2000/XP/2003/Vista (32/64-bit)
- Linux Kernel 2.6.x
- DOS DOS

#### Regulatory Approvals

- Hardware CE , FCC
- Software WHQL

#### Operation Environment

- Operation Temperature 0 to 60°C
- Operation Humidity 5 to 95% RH

[\[Return\]](#)