



ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTE:100%.
- 2.INSULATION RESISTANCE:DC 300V AT 10ms R>10MΩ
- 3.CONTACT RESISTANCE:<5Ω .

PIN ASSIGNMENT

AM	AF	COLOR
1 ———	1 ———	RED
2 ———	2 ———	WHITE
3 ———	3 ———	GREEN
4 ———	4 ———	BLACK
SHELL ———	SHELL ———	BRAID

1	UL 2725 #28*1PR+#20*2C+ADB OD:5.0mm(BLACK)	PCS	1
2	USB POWER TYPE 5V COLOR: BALCK	PCS	1
3	PVC MOLDED BLACK IN COLOD	PCS	1
4	USB B TYPE MALE SODER SHELL PLATED NICKEL CONTACT:G/F	PCS	1
NO.	DESCRIPTION	UNIT	QT'Y

UNLESS OTHERWISE SPECIFIED TOLERANCE
 ANG. ±5°
 0. ±0.5
 .0 ±0.3
 .00 ±0.2

SCALE: 1:1 UNIT: mm

DRAWN ERIC XU06/08/12

CHECKED

APPROVED

DATE 06/08/12

DRAWN NAME:

PRODUCT NO.

FILE NAME:

競捷UC61

A		06/08/12	APPROVED	PRODUCT NO.
REV.	DESCRIPTION	DATE	SIZE A4	REV. A