HOME SERIES

LINE INTERACTIVE UPS







PRODUCT FEATURES:

- Simulated sine wave
- Automatic activation when the mains supply is returned

- Silencing function in the battery mode
- Charging in the Stand-By mode
- Protection from overload, short circuit and discharge
- Built-in automatic voltage regulation module (AVR)
- Microchip control to provide high operational efficiency
- Automatic test with every activation of the device
- Fuse
- Elegant, home design

PRODUCT SPECIFICATION:

UPS topology	Line-interactive (VI)
Power	480 W
Apparent power	850 VA
Type of casing	Desktop
Number of outlets	2
Outlet type	Type F
Battery quantity	1
Connectors	RJ-45, RJ-11, USB 2.0 Type-B
Battery capacity	9 Ah
Battery type	Lead acid VRLA AGM
Battery runtime at 50% load	3,4 min
Battery runtime at 100% load	0,15 min
Input voltage range	from 145 up to 290 V
Input frequency range	from 45 up to 65 Hz
Output voltage	230 V
Output frequency	50 Hz
Waveform type	Modified sine wave
Transfer time	from 2 up to 6 ms
Software	No
Dimensions	283 x 95 x 140 mm
Weight	4,85 kg

0

NORMAL OVERLOAD

armac

