



ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance: 10ohm
3. Insulation Resistance: 5Mega ohm
4. Hi-Pot: 300V DC/10ms

Pin Assignment			
USB AM	SIGNAL NAME	COLOR	MICRO USB B
1	VBUS	RED	1
2	D-	WHITE	2
3	D+	GREEN	3
	ID	<RA_PLUG_ID	4
4	GND	BLACK	5
SHELL	SHIELD	DRIAN	SHELL

UNLESS OTHERWISE SPECIFIED TOLERANCE			
ANG.	±5°		
0.	±0.5		
.0	±0.3		
.00	±0.2		
SCALE:	NONE	UNIT:	mm
DRAWN	Xing Fa	07/10/30	DRAWN NAME:
CHECKED	ERIC	07/10/30	競捷 US85
APPROVED	/ /		
REV.	A	DATE	PRODUCT NO.
			FILE NAME:

6	CORE: $\phi 12 \times 25 \times \phi 5.6 \text{mm}$	PCS	1
5	MICRO USB B TYPE MALE SHELL PLATED NICKEL CONTACT:G/F	PCS	1
4	PVC MOLDED BLACK IN COLOR		
3	CABLE: 1P*28AWG+2C*26AWG+AL+D+B DD3.8 BLACK IN COLOR REV:3.0		
2	PVC 55P MOLDED BLACK IN COLOR		
1	USB-A TYPE MALE SHELL PLATED NICKEL CONTACT:G/F	PCS	1
NO.	DESCRIPTION	UNIT	QT'Y
A	USB-A MALE/MICRO USB B MALE MOLDED CABLE		07/10/30
REV.	DESCRIPTION		DATE