

Super-Speed USB3.0

PCI-e 2 port USB3.0

Features

- Supports PCI Express Base Specification Revision 2.0.
- Single-lane (x1) PCI Express throughput rates up to 5 Gbps.
- Compliant with Universal Serial Bus 3.0 specification Revision 1.0.
- Compliant with xHCI (eXtensible Host Controller Interface) specifications Revision 0.95.
- Supports simultaneous operation of multiple USB 3.0, USB 2.0 and USB 1.1 devices.
- Supports USB data transfer rate of 1.5/12/480/5000 Mbps.
- Expands two external USB3.0 Super-Speed ports on the system.
- Each USB port supplies maximum +5V / 900mA power output to USB device.
- Built-in 4-pin power connector for receiving extra power supply from system.
- Hot-swapping feature allows you to connect/disconnect devices without powering down the system.
- Driver supports for Microsoft Windows 2000, XP, Vista, and 7 operation system.

Express Card USB3.0

- Fully compliant with ExpressCard Specification 1.0.
- Full single-lane (or x1) PCI Express throughput.
- ExpressCard/34 form factor module.
- Compliant with Universal Serial Bus 3.0 specification Revision 1.0.
- Compliant with xHCI (eXtensible Host Controller Interface) specifications Revision 0.95.
- Supports simultaneous operation of multiple USB 3.0, USB 2.0 and USB 1.1 devices.
- Supports USB data transfer rate of 1.5/12/480/5000 Mbps.
- Expands two external USB3.0 Super-Speed ports on the system.
- Built-in DC Jack connector for receiving extra power to meet USB3.0 +5V/900mA power output standard.
- Hot-swapping feature allows you to connect/disconnect devices without powering down the system.
- Driver supports for Microsoft Windows 2000, XP, Vista, and 7 operation system.

