




ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. CONTACT RESISTANCE:100MHM
3. INSULATION RESISTANCE:5MEGA OHM
4. HIPOT TEST:300V/10MS

MC	F	AM	COLOR
1	—	1	— RED(PWR)
2	—	2	— WHITE(UTP_D-)
3	—	3	— GREEN(UTP_D+)
5	—	4	— BLACK(GND_PWRrt)
6	—	5	— YELLOW(SDP1-)
7	—	6	— BLUE(SDP1+)
8	—	7	— DRAIN(SDP1_Drain) (SDP2_Drain)
9	—	8	— ORANGE(SDP2-)
10	—	9	— PURPLE(SDP2+)
SHELL	—	SHELL	— BRAID

4	ABS MOLDING BLACK IN COLOR	1	pcs
3	55P PVC MOLDING BLUE IN COLOR	1	pcs
2	USB3.0 MICRO A+B TYPE FEMALE SHELL PLATED:NICKEL CONTACT:30U"	1	pcs
1	USB3.0 A TYPE MALE SHELL PLATED:NICKEL CONTACT:30U"	1	pcs
DESCRIPTION		Q'TY	UNIT
A		10/09/23	
REV.	DESCRIPTION	DATE	

UNLESS OTHERWISE SPECIFIED TOLERANCE			
ANG.	±5°		
0.	±0.5		
.0	±0.3		
.00	±0.2		
SCALE:	NONE	UNIT:	mm
DRAWN	Steven	10/09/23	DRAWN NAME:
CHECKED	Eric	10/09/23	競捷 UY21
APPROVED			PRODUCT NO.
			FILE NAME: