

**Features:**

- § Multiple video inputs to Multiple video outputs
- § Supports VGA, SVGA, XGA and Multi Sync monitors
- § Supports Audio Function
- § Supports 200 MHz video bandwidth
- § Supports resolution up to 1600X1200
- § RS-232 Compatible
- § Ideal for video broadcasting, remote monitoring, security monitoring, production and industrial control monitoring, educational facilities.
- § Convenient use with IR Remote Control (XPC84) and PS/2 Keyboard Control

**Specification:**

| Function              | Specification   |
|-----------------------|---|
| Model                 | 8 Inputs to 4 Outputs                                   |
| Input Side Connector  | HDD 15M x 8 (Monitor)                                   |
| Output Side Connector | HDD 15F x 4 (Monitor/Projector)<br>3.5mm Audio Jack x 4 |
| Audio Support         | Yes   |
| Max. Resolution       | 1600 x 1200   |
| Video Bandwidth       | 200MHz  |
| Horizontal Frequency  | 30-100KHz   |
| Vertical Frequency    | 43-120Hz  |
| Keyboard Control      | Yes   |
| IR Remote Control     | Yes   |
| Transmission Distance |   |
| PC to Switch          | 5 meters  |
| Monitor to Switch     | 15 meters   |
| Power Supply          | DC12V / 500mA   |
| Case Design           | Metal   |
| Weight                | 2.36kgs   |

**Application:**

