



PIN ASSIGNMENT

DVI 24+5M	RCA-F	RCA-F
C1	INTER RED	INTER RED
C2	INTER GREEN	INTER GREEN
C3	INTER BLUE	INTER BLUE
C5	OUTER RED	OUTER RED
	OUTER GREEN	OUTER GREEN
	OUTER BLUE	OUTER BLUE

ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTE:100%.
- 2.CURRENT RATING:1.5AMP.
- 3.INSULATION RESISTANCE:DC 300V AT 10ms R5M Ω
- 4.CONTACT RESISTANCE:10 Ω.

No.	DESCRIPTION	UNIT	Q'TY
5	THUMB SCREW #4-40UNC PLATED:GOLD ABS COLOR:BLACK	PCS	2
4	DVI 24+5 MALE SOLDER COLOR:BLACK SHELL PLATED:GOLD	PCS	1
3	PVC MOLDED BLACK IN COLOR		
2	RCA FEMALE<RED,GREEN,BLUE> PLATED:GOLD	PCS	6
1	UL2919 COAXIA*3 28AWG COLOR:BLACK	PCS	1

UNLESS OTHERWISE SPECIFIED TOLERANCE ANG. ±5° 0. ±0.5 .0 ±0.3 .00 ±0.2			
SCALE: NONE	UNIT: mm		
DRAWN HUANGYU	08/06/09	DRAWN NAME: 競捷—VG51	
CHECKED Eric	08/06/09	PRODUCT NO.	
APPROVED / /		FILE NAME:	
DATE 08/06/09		SIZE A4	REV. A

REV.	DESCRIPTION	DATE
A		08/06/09