



RCA F

HD15M

PIN ASSEMBLY

ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTE:100%.
- 2.CURRENT RATING:1.5AMP.
- 3.INSULATION RESISTANCE:DC 300V AT 10ms R5M Ω
- 4.CONTACT RESISTANCE:10 Ω

	HD15M	RCA-F	RCA-F
	1	INTER RED	INTER RED
	6	OUTER RED	OUTER RED
SHIELD	2	INTER GREEN	INTER GREEN
	7	OUTER GREEN	OUTER GREEN
	3	INTER BLUE	INTER BLUE
	8	OUTER BLUE	OUTER BLUE

6	HIGH DENSITY D-SUB 15P MALE SOLDER INSULATOR COLOR:BLACK SHELL GOLD	PCS	1
5	PVC MOLDED BLACK IN COLOR		
4	THUMB SCREW #4-40UNC PLATED:GOLD ABS COLOR:BLACK	PCS	2
3	LOW DENSITY PE MOLDED		
2	RCA FEMALE<RED,GREEN,BLUE> PLATED:GOLD	PCS	6
1	UL2919 COAXIA*3 28AWG COLOR:BLACK	PCS	1
No.	DESCRIPTION	UNIT	Q'TY

UNLESS OTHERWISE SPECIFIED TOLERANCE		
ANG.	±5°	
0.	±0.5	
.0	±0.3	
.00	±0.2	
SCALE:	NONE	UNIT: mm
DRAWN	HUANGYU	08/06/09
CHECKED	ERIC	08/06/09
APPROVED	/ /	PRODUCT NO.
		FILE NAME:

競捷-VG52

A		08/06/09
REV.	DESCRIPTION	DATE

SIZE A4 REV. A