

LED Double Mirror Canning Light

Thank you for using the company's LED series of stage lights, in the boot before you check the voltage to the safe operation of this product.

Technical parameters:

Voltage: AC220V **Frequency:** 50/60HZ **Power:** 50W

Source: 5mmLED128 teeth (red 64, green 24, blue 40)

Control mode: self, voice, DMX512, and master-slave control

Channel: 6 channel **Packing:** 395mm * 235mm * 200mm **Net weight:** 4.3kg

Address code function:

ON	OFF	function
	123456789 10	patterns of activity from walking cycle operation 1-50
9	12345678 10	Sound sensitivity adjustable (silent delay closed-ray)
10	123456789	DMX-512-6-channel control ID = 1
5.10	12346789	DMX-512-6-channel control ID = 2
6.10	12345789	DMX-512-6-channel control ID = 3
5.6.10	1234789	DMX-512-6-channel control ID = 4
7.10	12345689	DMX-512-6-channel control ID = 5*
5.7.10	1234689	DMX-512-6-channel control ID = 6
.....
10	123456789	ID=1 CH1 control A map CH6 speed control LED
1.10	23456789	ID=1 CH2 control A map CH7 speed control LED
2.10	13456789	ID=1 CH3 control A map CH8 speed control LED
1.2.10	3456789	ID=1 CH4 control A map CH9 speed control LED
3.10	12456789	ID=1 CH5 control A map CH10 speed control LED
1.3.10	2456789	ID=1 CH6 control A map CH11 speed control LED
2.3.10	1456789	ID=1 CH7 control A map CH12 speed control LED
.....
12345678 10	9	from the machine (master-slave control) 17 channels

Note: The master-slave control, the host for self-propelled or voice, from the machine run simultaneously with the host

Access control parameters:

Channel	data	function
1CH	0	right power reversal
	1-200	0-360 degree of control (1.8 degrees site)
	201-255	Right power is transferred
2CH	0	left power reversal
	1-200	0-360 degree of control (1.8 degrees site)
	201-255	left power is transferred
3CH	0-255	motor rotation speed (0 - fast, 255 - slow)
4CH	0-255	50 different patterns choose the right
5CH	0-255	50 different patterns choose the left
6CH	0-255	pattern rotation speed

Warning: This product plus a watchdog program, Please do not open the board, if the watchdog to protect human factors (Death) phenomenon is not in warranty!

Note: This product downtime can not exceed six months, otherwise it would be a watchdog action.